HIDEOUT

Base Color Waterborne **Intense White**



- Provides excellent base for Ultra-Clear[™] or Traction[®]
- Quick-leveling, low-foam formula excellent for roller application
- Complete hide in 1-2 coats
- Excellent compatibility with Roll-on®, Ultra-Clear™,

Traction®, Crimp Coat™, and most latex enamels

- Low-odor, non-flammable, water-based
- Easy water clean-up
- High-gloss finish

CAUTION: Hideout™ is a pre-coating designed as a laminate in Traction® Skate Floor Coating systems and should never be subjected to foot traffic or skated on without completing approved top coatings.

DIRECTIONS: Refer to Hideout™ brochure for complete preparations and application instructions.

Although thorough screening may be sufficient, an approved primer or laminate coating should be applied to previously coated surfaces. We recommend Crimp Coat™ Laminating Primer.

1.For newly installed floors, follow manufactures recommendations for approved primers and sealers before application.

2. Application by roller or airless sprayer is recommended. For rolling instructions, see Hideout™ brochure for details and procedures.

- 3. Coverage averages 800 square feet per gallon.
- 4.One hour dry time, recoat in two hours.

5.After 4 hours drying, sanding or light screening recommended 6.Apply Circles and Lines using recommended acrylic latex enamels.

7.Clean up with soap and water. 8.Protect from freezing.





Roll-On Floor Systems, LLC 233 WEST PIPELINE ROAD HURST, TEXAS 76053 Phone 817-267-6631 www.roll-on.com

Properties

Density - 10.2 lbs/gal Viscosity - 2000 - 4000 cP (Brookfield) Solids - 44 - 46% TiO2 - 17% Coverage - 800 sq. ft./gal Dry Time – 1 hour Recoat Time – 2 hours VOC - 150 g/L Meets Strict Clean Air Requirements: VOC (minus water) < 340 grams/liter. Classification: Architectural Floor Coating. Thinning Instructions: Do not thin.

Meets Strict Clean Air Requirements: VOC (minus water) < 340 grams/liter. Classification: Industrial Maintenance Coating. Thinning Instructions: Do not